

# Mini mount-under front camera

CAM-E-309F

## Delivery content



## Product features

- Mini mount-under front camera
- Sensor type 1/4inch CMOS
- Picture format NTSC colour
- Resolution 720 x 480 pixel
- Min illumination 0.5 Lux
- Angle h=185°, v=80°, d=205°
- Unmirrored picture (fixed)
- System cable with throughput, e.g. for reverse signal
- Protection class IP69K
- Suitable for permanent operation
- Holder and camera colour black
- Total cable length about 8.80m
- Video connector RCA male connector
- System connector camera 4pin BM
- Diameter camera connector 5mm
- Operating voltage +12V DC (9~ 16V)
- Current consumption 100mA
- Operating temperature range -40°C to +85°C
- Weight incl. cable 218g
- Dimensions camera only  
40 x 23 x 23mm (L x W x H)
- Dimensions camera with holder  
40 x 33 x 30mm (L x W x H)

## Installation

Mount-under installation



**Note:** With the supplied holder, the camera can not be mounted on top.

## Connection cable



- Video signal
- +12V power supply output from interface for front camera or ACC
- Throughput
- Ground

**In case the isolation of the camera is harmed in the moisture section close to the camera, it is mandatory to repair the isolation. Otherwise the camera will inevitably become moist inside sooner or later.**



10R-05 11466

